



4 wheel drive



Heavy duty 3 point linkage system



John Deere PowerTech™Engine





For large implements



Features



Spacious Operator Station

Ergonomically designed operator station controls help in reducing fatigue and improving efficiency.



Power Core Air Filter®

Dual element with add-on pre-cleaner. Ensures 99.99% clean air.



Dual Speed PTO

Use 540 and 1000 RPM, according to the need of the implement.



High Lifting Capacity

Unparalleled 3650 kgf lifting capacity is useful for lifting heavy implements with greater ease.



Isolated Sealed Glass Cabin

Gives comfort to the driver in long working hours. Protects the operator from noise & dust and provides 320° visibility.



International Looks

Attractive hood profile with a chrome finish gunsight, eye pleasing contours and excellent paint finish; everything designed to contribute to its stunning looks.



Steps and Handrail

Steps and Handrail on both sides for comfortable entry and exit.



Speed Options 12 F + 4 R

Appropriate speed selection for each application.



Large lockable doors on both sides

Excellent overall visibility in all applications due to lockable, transparent glass doors of the cab. The large doors open wide, almost up to 70° and smoothly for easy entry and exit of the operator.

Applications



Technical Specifications

ENGINE

Air filter

Type : 120 HP (89.5 kW),

4 Cylinders Turbo Charged High pressure common rail with electronically controlled fuel injection unit, PowerTech™ engine

: Dual element with add-on

pre-cleaner.

TRANSMISSION

Type : Synchromesh Transmission (TSS)

Clutch : Dual

Gear box : 12 Forward + 4 Reverse Speeds : Forward 3.1 - 30.9 kmph Reverse 6.0 - 31.9 kmph

BRAKES

Type : Oil Immersed Disc Brakes

HYDRAULICS

Maximum Lifting capacity: 3650 kgf 3 point linkage: Category - II

Automatic depth & draft control

(ADDC)

STEERING

Type : Power

POWER TAKE OFF

Type : Independent,

6 Splines / 21 Splines Dual Speed PTO

RPM : 540 RPM / 1000 RPM

WHEELS AND TYRES

Front : 14.9 x 24 (0.38 x 0.61 m) Rear : 18.4 x 38 (0.47 x 0.97 m)

FUEL TANK

Capacity : 220 L

ELECTRICAL SYSTEM

: 135Ah, 12 V battery, 90 Amp. alternator, 12 V, 2.5 kW Starter motor

DIMENSIONS AND WEIGHT

Total weight : 4500 kg
Wheel base : 2560 mm
Overall length : 4410 mm
Overall width : 2300 mm
Ground clearance : 0470 mm

ACCESSORIES

Ballast weights: Front - Max. 12 nos. x 50 kg each

Rear - Max. 8 nos. x 55 kg each

ADDITIONAL FEATURES

Standard 2 SCVs

Also Available in 110 HP 6110B Model

Introducing...

Super Heavy Duty

Tractor
For large implements





John Deere Genuine Parts

I Economical I Reliable I Easily available I



John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in


For more information, please contact our authorised dealer or nearest area office.











• Harvesters • Finance

