NEO BY EULER | HiLOAD EV 2.0 XR

Ab Naye HiLOAD EV Ke Sath

223 km* ki Certified Range

Zyada Range, Zyada Trips aur Zyada Kamai



BATTERY WARRANTY
8 Years
2 Lakh km*
SEAL OF TRUST

155+ km*	**12.96 kWh**	**672 kg**	**78 Nm**	**7 (Rear Side)**
*RealRange™	Battery	Payload for PV Variant	Torque	Leaf Spring

*Range under standard test conditions. Actual range may vary based on load, terrain & driving conditions.

NEO BY EULER | HiLOAD EV 2.0 XR



3 free services up to 20,000 km.

Efficient Air Duct: Designed to provide proper ventilation.

1800 1238 1238 (Toll Free Number)

www.neo.eulermotors.com

Official Address: A-39, Near Pocket C, Block B,
Mohan Cooperative Industrial Estate, Badarpur,
New Delhi - 110044.

MGI EULER

MALAPPURAM Tel: 7592979700
WAYANAD Tel: 7594979700
PALAKKAD Tel: 9633979700

SCAN THE QR CODE TO VISIT OUR WEBSITE

	HiLOAD EV 2.0 XR
Performance	
Certified Payload	672 kg (PV) / 592 kg (DV)
Kerb Weight (without Driver) (kg)	611 kg (PV) / 687 kg (DV)
Gross Vehicle Weight (kg)	1350 kg
Certified Range	223 km
RealRange™*	155+ km*
Top Speed	52 km/h
Charging System	3.3 kW On-board charger
Charging Time (0~100%)	4 hrs 30 min
Battery Powerpack	
Battery Chemistry / Type	Lithium-ion Battery, 86.4 V
Battery Capacity	12.96 kWh
Battery Warranty*	6 years / 1.5 Lakh km (Standard Warranty) / 8 Years / 2 Lakh km (Extended Warranty)
Description	
Seating Capacity	D + Cargo
Ground Clearance (mm)	140 mm (Rigid Axle)
Track Width (mm)	1260 mm
Wheelbase (mm)	2260 mm
Gradeability	28%
Variant	
Overall Length (mm)	DV 120: 3485 mm, DV 170: 3597 mm PV & HD 120: 3455 mm
Overall Width (mm)	DV 120: 1460 mm (Load Body) | DV 170: 1552 mm (Load Body)
Overall Height (mm)	HD & DV 120: 2090 mm PV 120: 1875 mm | DV 170: 2289 mm
Container Dimension (lxbxh) mm	DV 120 Cubic mm: 1853 × 1463 × 1548 mm DV 170 Cubic mm: 1965 × 1555 × 1585 mm
Motor	
Power (peak)	11 kW
Torque (peak)	78 Nm
Hill Hold Assist	Yes
Brake Systems	
Front	Hydraulic Disc Brake
Rear	Hydraulic Drum Brake
Suspension Systems	
Front	Dual Hydraulic Shock Absorber with Helical Spring
Rear	Rigid Axle with Leaf Spring
Drive Modes	Range | Thunder
Telematics / Connectivity	Shepherd App: Location, Reverse Parking Sensor, Reverse Camera, Digi Lock, Geofencing, Service Tracking & Booking
Water Wading / Resistance	IP67, 250 mm
Headlights	LED with DRLs
Tyres	R12 130/80 Radial Tubeless

RealRange™ : Real Range means the distance your electric vehicle can travel on a full charge under normal conditions.
This distance is an estimate based on actual usage conditions.

*Certified Range is always higher than RealRange™ because it is tested under controlled laboratory conditions (IDC method)
with light load and controlled driving.

**Normal conditions include factors such as vehicle speed and braking rate, battery health, road and traffic